



General ordering data

Order No.	1021500000
Short text for material	WDK 2.5
EAN	4008190169527
Qty	100

IEC/EN 60079-7 rating data

Certificate No.	KEMA98ATEX1687U
ATEX certificate	KEMA98ATEX1687U_d.pdf
Download English	KEMA98ATEX1687U_e.pdf
Certificate No.	IECEXULD05.0008U
IEC Ex certificate	IECEXULD05.0008U_e.pdf
max. voltage	275 V
Current	21 A
Conductor cross-section, max.	2.5 mm ²
max. voltage	275 V
Current	20 A
Conductor cross-section, max.	2.5 mm ²
Voltage when using cross-connections	CrossConnectionGuide.pdf
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity
Marking EN 60079-7	Ex e II
Marking ATEX Directive 94/9/EC	Ex II 2 G D

Additional technical data

Type of connection	screwed
No. of identical terminals	1
Version	Double terminal
Type of mouting	clipped
UL 94 flammability rating of insulation material	V-0
Installation advice	TS 35
Colour of insulating material	dark beige
Insulating material	Wemid
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Connection direction	on side
Product range	W-Series
No. of levels	2
Levels cross-connected internally	No
No. of terminal strips per level	2
Explosion-tested version "Ex e"	Yes
End plate required	Yes

CSA rating data

Voltage CSA	300 V
Max. cross-section (CSA)	AWG 12
CSA current	10 A
Min. cross-section (CSA)	AWG 26

Conductors for clamping (1) with equal cross-section (rated connection)

Flexible with ferrule, max. (DIN 46228 pt 1)	1,5 mm ²
Flexible, max.	1,5 mm ²
Solid, max.	1,5 mm ²
Solid, min.	0,5 mm ²
Flexible with ferrule, min. (DIN 46228 pt 1)	0,5 mm ²
Flexible, min.	0,5 mm ²

Conductors for clamping (rated connection)

Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A3
AWG conductor size, max.	3,31 mm ²
AWG conductor size, max.	AWG 12
Stranded, max.	4 mm ²
Stranded, min.	1,5 mm ²
AWG conductor size, min.	0,05 mm ²
AWG conductor size, min.	AWG 30
Flexible, min.	0,5 mm ²
2nd type of connection	screwed
Solid, min.	0,5 mm ²
Stripping length	10 mm
Type of connection	Screw connection
No. of connections	4
Torque level with DMS electric screwdriver	1
Tightening torque range	0.4...0.6 Nm
Solid, max.	4 mm ²
Flexible, max.	4 mm ²
flexible w. ferrule AEH, max. DIN 46228-1	2,5 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2,5 mm ²
flexible w. ferrule AEH, min. DIN 46228-1	0,5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0,5 mm ²
Clamping range, max.	4 mm ²
Clamping range, min.	0,05 mm ²
Clamping screw	M 2.5
Connection direction	on side

Dimensions

Weight	14,00 g
TS 35 offset	19 mm
Height of lowest version	63 mm
Length	69 mm
Width	5,1 mm

Disconnect terminals

Torque level with DMS electric screwdriver	1
--	---

Rating data

Rated cross-section	2,5 mm ²
Rated voltage	400 V
Rated impulse withstand voltage	6 kV
Rated current	24 A
Norm	IEC 60947-7-1
Current with max. conductor	32 A
Pollution severity	3

UL rating data

Voltage UL	300 V
Current (UL)	20 A
Max. cross-section (UL)	AWG 12
Min. cross-section (UL)	AWG 30

Approvals

Approvals



Approvals



CSA;GOST;0344;UL/UR;EX;CE;

Approvals

Approvals

**Downloads**

STEP	1021500000_12436_WDK_2.5_STP
------	------------------------------

Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Identical profiles from 2.5 to 10 mm² with uniform end and partition plates. An unsurpassed combination of many

advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

Related products

Order No.	Short text for material
1029100000	WDK 2.5/800V
1021580000	WDK 2.5 BL
1036400000	WDK 2.5DU-PE
1041100000	WDK 2.5 ZQV
1041180000	WDK 2.5 ZQV BL
1025610000	WDK 2.5 ZQV/10/BEZ
1022300000	WDK 2.5V
1022380000	WDK 2.5V BL
1022350000	WDK 2.5V GE
1022360000	WDK 2.5V OR