



General ordering data

Order No.	1036100000
Short text for material	WDU 16N
EAN	4008190273217
Qty	50

Additional technical data

Type of connection	screwed
No. of identical terminals	1
Version	Feed-through terminal
Type of mouting	clipped
UL 94 flammability rating of insulation material	V-0
Installation advice	TS 35
Colour of insulating material	dark beige
Insulating material	Wemid
Open sides	closed
Operating temperature range	- 50 °C, + 120 °C
Connection direction	on side
Product range	W-Series
No. of levels	1
Levels cross-connected internally	No
No. of terminal strips per level	2
Explosion-tested version "Ex e"	No
End plate required	No

CSA rating data

Voltage CSA	300 V
Max. cross-section (CSA)	AWG 6
CSA current	70 A
Min. cross-section (CSA)	AWG 14

Conductors for clamping (1) with equal cross-section (rated connection)

Flexible with ferrule, max. (DIN 46228 pt 1)	4 mm ²
Solid, min.	1,5 mm ²
Solid, max.	4 mm ²
Flexible, max.	4 mm ²
Flexible with ferrule, min. (DIN 46228 pt 1)	1,5 mm ²
Flexible, min.	1,5 mm ²

Conductors for clamping (rated connection)

Flexible, min.	1,5 mm ²
2nd type of connection	screwed
Solid, min.	1,5 mm ²
Stripping length	12 mm
Type of connection	Screw connection
No. of connections	2
Torque level with DMS electric screwdriver	4
Tightening torque range	1.2...2.4 Nm
Solid, max.	16 mm ²
Flexible, max.	16 mm ²
flexible w. ferrule AEH, max. DIN 46228-1	16 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	16 mm ²
flexible w. ferrule AEH, min. DIN 46228-1	1,5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	1,5 mm ²
Clamping range, max.	25 mm ²
Clamping range, min.	1,5 mm ²
Clamping screw	M4
Blade size	1.0 x 5.5 mm
Gauge to IEC 60947-1	B7
AWG conductor size, max.	13,30 mm ²
AWG conductor size, max.	AWG 6
Stranded, max.	25 mm ²
Stranded, min.	1,5 mm ²
AWG conductor size, min.	2,08 mm ²
AWG conductor size, min.	AWG 14
Connection direction	on side

Dimensions

Weight	24,85 g
TS 35 offset	15 mm
Height of lowest version	47 mm
Length	60 mm
Width	12 mm

Disconnect terminals

Torque level with DMS electric screwdriver	4
--	---

Rating data

Rated cross-section	16 mm ²
Rated voltage	690 V
Rated impulse withstand voltage	8 kV
Rated current	76 A
Norm	IEC 60947-7-1
Current with max. conductor	101 A
Pollution severity	3

UL rating data

Voltage UL	300 V
Current (UL)	70 A
Max. cross-section (UL)	AWG 6
Min. cross-section (UL)	AWG 14

Approvals

Approvals	
-----------	---

Approvals

Approvals	
-----------	---

Downloads

STEP	1036100000_21921_WDU_16N_ST
------	-----------------------------

Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-20
eClass 5.0	27-14-11-20
eClass 5.1	27-14-11-20

Identical profiles from 2.5 to 10 mm² with uniform end and partition plates. An unsurpassed combination of many advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

Related products

Order No.	Short text for material
1036180000	WDU 16N BL



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[WDU_16N](#)

EN
This Datasheet is presented by
the manufacturer

DE
Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR
Cette fiche technique est
présentée par le fabricant